



MODELS PCD110X, PCD110XM, PCD110XH, PCD110XMH, & PCD110XIAQS

CEILING MOUNT BATHROOM FANS WITH DC MOTOR

Features and Construction

- Extremely quiet operation <0.3 Sones
- Brushless DC Motor for long life - rated for 60,000 hours continuous on
- PCD110XM has a built-in motion sensor
- PCD110XH has a built-in humidity sensor
- PCD110XMH has a built-in motion sensor and humidity sensor
- PCD110XIAQS detects VOCs and/or rapid rise in humidity
- High/Low speed delay timer
- Built-in backdraft damper
- Robust steel housing
- Attractive, sturdy grille
- ETL Listed
- ENERGY STAR® qualified
- HVI Certified
- 6 year warranty



Performance and Dimensions

PCD110X (All Variations, H, M, MH, IAQS)					
CFM @ 0.1" SP	40	90	110	120	140
CFM @ 0.25" SP	-	51	78	91	113
Sones @ 0.1" SP	<0.3	0.5	0.9	1.2	1.5
Watts @ 0.1" SP	4.2	8.1	10.3	12.2	15.6
Watts @ 0.25" SP	-	7.9	10.3	12.5	15.7
Energy Efficiency (CFM/Watt) 0.1" SP	9.6	12.2	11.4	10.8	9.4
Energy Efficiency (CFM/Watt) 0.1" SP	-	6.5	7.6	7.3	7.2
Amps	0.09	0.16	0.20	0.22	0.27
ENERGY STAR Qualified	Yes				
Duct Connector Diameter (in)	6"				
Grille Size (in)	13" x 14"				
Dimensions (w x d x h) (in)	11-3/8" x 10-1/2" x 7-5/8"				

You CHOOSE Your Airflow!

The built-in **Toggle Switches** and duct connector options allow you to set the fan to the needed airflow.

90	110	120	140
6"	6"	6"	6"

Factory setting is 110 CFM with 6" duct

Integrated Controls

