

PC110X-2S

2-Speed Premium Choice Fan

(Ceiling Mounted Ventilation Fans)



Performance

Model	Duct Size for Test	CFM (High Speed)		CFM (Low Speed)	Energy Efficiency	Watts	Power	Sones		Amps
		0.1" SP	0.25" SP	0.1" SP	(CFM/ Watts)		(V/Hz)	High Speed	Low speed	
PC110X-2S	4"	100	88	40	3.3	33	120/60	1.2	0.3	0.4
	6"	110	100	50				0.9	0.3	

Dimensions

Model	Duct Dia.	Grille Size (Sq. in inches)	С	Unit Wgt.		
			W	D	Н	(lbs)
PC110X-2S	4 or 6"	13 x 14	11-3/8	10-1/2	7-5/8	9







Typical Specifications:

Ventilating fan shall be S&P PC110X-2S mounted in the ceiling. The fan shall have a 5 year limited warranty. The fan shall be HVI Certified at 0.1 inch water gauge for CFM performance above. The motor shall be ETL and cETL Listed with impedance protection plus additional thermal protection. The fan shall be Energy Star Qualified.

For more information contact us at www.solerpalau-usa.com or 1.800.961.7370 for additional submittal drawings. S&P will not be responsible for fabrication changes or errors resulting from customer use of a non-current submittal drawing.

